



**SERVICE ROAD RECONSTRUCTION**  
**ONEIDA PROJECT NO. F55-43305**  
**IRR ROUTE NO. 5032 & 5028**

**ONEIDA INDIAN RESERVATION**  
**OUTAGAMIE AND BROWN COUNTY, WISCONSIN**

**GRADING, DRAINAGE, AGGREGATE BASE, CURB AND GUTTER, BITUMINOUS SURFACE**

**GROSS LENGTH OF CENTER LINE** 1156.00'  
**EXEMPTIONS** 0.00'  
**NET LENGTH OF CENTER LINE** 1156.00'

INDIAN CLAIM 146, 153, AND 153A


T23N R19E

OUTAGAMIE AND BROWN COUNTY

STATE OF WISCONSIN



**CONVENTIONAL SYMBOLS**



**PROFILE**

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE  
(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

UTILITIES

ELECTRIC

FIBER OPTIC

GAS

SANITARY SEWER

STORM SEWER

TELEPHONE

WATER

UTILITY PEDESTAL

POWER POLE

TELEPHONE POLE

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE

(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

UTILITIES

ELECTRIC

FIBER OPTIC

GAS

SANITARY SEWER

STORM SEWER

TELEPHONE

WATER

UTILITY PEDESTAL

POWER POLE

TELEPHONE POLE

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE

(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

UTILITIES

ELECTRIC

FIBER OPTIC

GAS

SANITARY SEWER

STORM SEWER

TELEPHONE

WATER

UTILITY PEDESTAL

POWER POLE

TELEPHONE POLE

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE

(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

UTILITIES

ELECTRIC

FIBER OPTIC

GAS

SANITARY SEWER

STORM SEWER

TELEPHONE

WATER

UTILITY PEDESTAL

POWER POLE

TELEPHONE POLE

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE

(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

UTILITIES

ELECTRIC

FIBER OPTIC

GAS

SANITARY SEWER

STORM SEWER

TELEPHONE

WATER

UTILITY PEDESTAL

POWER POLE

TELEPHONE POLE

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE

(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

UTILITIES

ELECTRIC

FIBER OPTIC

GAS

SANITARY SEWER

STORM SEWER

TELEPHONE

WATER

UTILITY PEDESTAL

POWER POLE

TELEPHONE POLE

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE

(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

UTILITIES

ELECTRIC

FIBER OPTIC

GAS

SANITARY SEWER

STORM SEWER

TELEPHONE

WATER

UTILITY PEDESTAL

POWER POLE

TELEPHONE POLE

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE

(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

UTILITIES

ELECTRIC

FIBER OPTIC

GAS

SANITARY SEWER

STORM SEWER

TELEPHONE

WATER

UTILITY PEDESTAL

POWER POLE

TELEPHONE POLE

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE

(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

UTILITIES

ELECTRIC

FIBER OPTIC

GAS

SANITARY SEWER

STORM SEWER

TELEPHONE

WATER

UTILITY PEDESTAL

POWER POLE

TELEPHONE POLE

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE

(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

UTILITIES

ELECTRIC

FIBER OPTIC

GAS

SANITARY SEWER

STORM SEWER

TELEPHONE

WATER

UTILITY PEDESTAL

POWER POLE

TELEPHONE POLE

GRADE LINE

ORIGINAL GROUND

MARSH OR ROCK PROFILE

(To be noted as such)

SPECIAL DITCH

GRADE ELEVATION

CULVERT (Profile View)

</div

# STATEMENT OF ESTIMATED QUANTITIES

ITEM NUMBER	NOTES	ITEM NAME	UNIT	ESTIMATED QUANTITIES	FINAL QUANTITIES
204.0150		REMOVING CURB AND GUTTER	LF	526	
204.0155		REMOVING CONCRETE SIDEWALK	SY	113	
204.0210		REMOVING MANHOLES	EACH	3	
204.0220		REMOVING INLETS	EACH	2	
204.0245		REMOVING STORM SEWER 12 INCH	LF	351	
204.0245		REMOVING STORM SEWER 18 INCH	LF	60	
205.0100		EXCAVATION COMMON	CY	7,283	
213.0100		FINISHING ROADWAY (PROJECT)	EACH	1	
305.0110		BASE AGGREGATE DENSE 3/4-INCH	TON	86	
305.0120		BASE AGGREGATE DENSE 1 1/4-INCH	TON	2,600	
311.0110		BREAKER RUN	TON	3,900	
416.0170		CONCRETE DRIVEWAY 7 INCH	SY	59	
455.0105		ASPHALTIC MATERIAL PG58-28	TON	58	
455.0605		TACK COAT	GAL	107	
460.1103		HMA PAVEMENT TYPE E-3	TON	960	
465.0120		ASPHALTIC SURFACE DRIVEWAYS AND FIELD ENTRANCE	TON	100	
521.0124		CULVERT PIPE CORRUGATED STEEL 24 INCH	LF	24	
601.0411		CONCRETE CURB AND GUTTER 30-INCH TYPE D	LF	3,130	
602.0405		CONCRETE SIDEWALK 4 INCH	SF	6,120	
602.0515		CURB RAMP DETECTABLE WARNING FIELD NATURAL PATINA	SF	48	
608.0312		STORM SEWER PIPE REINFORCED CONCRETE CLASS III 12 INCH	LF	478	
608.0324		STORM SEWER PIPE REINFORCED CONCRETE CLASS III 24 INCH	LF	979	
611.0201.S		MANHOLE TYPE 1 SPECIAL	EACH	6	
611.0303		INLET TYPE 3	EACH	8	
611.0612		INLET COVER TYPE C	EACH	14	
611.8110		ADJUSTING MANHOLE COVERS	EACH	5	
619.1000		MOBILIZATION	EACH	1	
625.0100		TOPSOIL	SY	3,300	
628.1504		SILT FENCE	LF	430	
628.1520		SILT FENCE MAINTENANCE	LF	430	
628.1905		MOBILIZATIONS EROSION CONTROL	EACH	1	
628.1910		MOBILIZATIONS EMERGENCY EROSION CONTROL	EACH	1	
628.2002		EROSION MAT CLASS I TYPE A	SY	3,300	
628.7010		INLET PROTECTION TYPE B	EACH	5	
628.7015		INLET PROTECTION TYPE C	EACH	14	
628.7504		TEMPORARY DITCH CHECKS	LF	20	
629.0210		FERTILIZER TYPE B	CWT	2	
630.0140		SEEDING MIXTURE NO. 40	LB	76	
630.0200		SEEDING TEMPORARY	LB	89	
634.0612		POSTS WOOD 4X6 INCH 12 FEET	EACH	6	
637.0202		SIGNS REFLECTIVE TYPE II	SF	19	
638.2602		REMOVING SIGNS TYPE II	EACH	8	
638.3000		REMOVING SMALL SIGN SUPPORTS	EACH	6	
643.0100		TRAFFIC CONTROL PROJECT	EACH	1	
646.0106		PAVEMENT MARKING EPOXY 4 INCH	LF	2,928	
647.0766		PAVEMENT MARKING CROSSWALK EPOXY 6 INCH	LF	140	
650.4000		CONSTRUCTION STAKING STORM SEWER	EACH	14	
650.4500		CONSTRUCTION STAKING SUBGRADE	LF	1,700	
650.5000		CONSTRUCTION STAKING BASE	LF	1,700	
650.5500		CONSTRUCTION STAKING CURB AND GUTTER	LF	1,700	
650.9920		CONSTRUCTION STAKING SLOPE STAKING	LF	1,700	
690.0150		SAWING ASPHALT	LF	955	
690.0250		SAWING CONCRETE	LF	10	
SPV.0900.00		CONTRACTOR SAMPLING AND TESTING	EACH	1	
SPV.0900.01		CONSTRUCTION SCHEDULE	EACH	1	
SPV.0900.02		PROJECT REPRESENTATIVE	EACH	1	
SPV.0900.03		ADJUSTING WATER VALVE	EACH	5	

## BASIS OF ESTIMATED QUANTITIES

BITUMINOUS MATERIAL FOR MIXTURE	6% BINDER, 6% WEARING
WEARING COURSE MIXTURE	112 lbs./ S.Y./ inch
BINDER COURSE MIXTURE	112 lbs./ S.Y./ inch
AGGREGATE BASE COURSE	1.95 ton/ C.Y. ASSUMED 3% MOISTURE AS PRODUCED IN PIT
FERTILIZER TYPE B	64.5 POUNDS PER 1000 SQUARE YARDS
SEEDING, MIXTURE NO. 40	18.5 POUNDS PER 1000 SQUARE YARDS + 25%
TEMPORARY SEEDING	27 POUNDS PER 1000 SQUARE YARDS

## STANDARD DETAIL DRAWINGS

FACILITIES DEVELOPMENT MANUAL WISCONSIN DEPARTMENT OF TRANSPORTATION	
ITEM	DRAWING NO.
INLET COVERS	S.D.D. 8 A 5-18a
INLET COVERS	S.D.D. 8 A 5-18b
MANHOLES TYPE 1	S.D.D. 8 B 6-4
INLET	S.D.D. 8 C 1-5
CONCRETE CURB & GUTTER	S.D.D. 8 D 1-17
CURB RAMPS1	S.D.D. 8 D 5-15b
SILT FENCE	S.D.D. 8 E 9-6
INLET PROTECTION	S.D.D. 8 E 10-2

## UTILITIES

TELEPHONE
SBC
205 S. JEFFERSON ST., P.O. BOX 10
GREEN BAY, WI 54305
PHONE: (920) 443-4129
CONTACT PERSON: BRET LAFAVE

GAS
WISCONSIN PUBLIC SERVICE
600 NORTH ADAMS STREET
GREEN BAY, WI 54301
PHONE: (920) 617-5127 (GAS)
CONTACT PERSON: JERRY PEOT (GAS)

ELECTRIC
WISCONSIN PUBLIC SERVICE
600 NORTH ADAMS STREET
GREEN BAY, WI 54301
PHONE: (877) 444-0888 (ELEC)
CONTACT PERSON: MIKE VALLESKY (ELEC)

ONEIDA TRIBE OF INDIANS
UTILITIES DEPARTMENT
P.O. BOX 365
ONEIDA, WI 54155
PHONE: (920) 869-1600
CONTACT PERSON: SCOTT COTTRELL

TELEVISION
TIME WARNER
1001 W. KENNEDY AVE., P.O.BOX 145
KIMBERLY, WI 54136
PHONE: (920) 749-1400
CONTACT PERSON: LARRY PILSTRUM

ONEIDA TRIBE OF INDIANS
DEPARTMENT OF PUBLIC WORKS
P.O. BOX 365
ONEIDA, WI 54155
PHONE: (920) 869-1059
CONTACT PERSON: MIKE FINN

TO OBTAIN LOCATION OF  
PARTICIPANTS' UNDERGROUND  
FACILITIES BEFORE YOU  
DIG IN WISCONSIN

CALL DIGGER'S HOTLINE  
1-800-242-8511

TOLL FREE

TELEFAX 1-800-338-3860  
TDD (FOR HEARING IMPAIRED) 1-800-542-2289

WIS. STATUTE 182.0175 (1974)  
REQUIRES MINIMUM OF 3 WORK DAYS  
NOTICE BEFORE YOU EXCAVATE

ESTIMATED QUANTITIES – ROADWAY & DRAINAGE  
ONEIDA TRIBE OF INDIANS OF WISCONSIN  
SERVICE ROAD RECONSTRUCTION

DATE  
8/1213  
OTIE  
SHEET NO.  
2



EARTHWORK				
LOCATION	CUT VOLUME	FILL VOLUME	EXPANDED FILL	NET VOLUME
	C.Y.	C.Y.	C.Y.	C.Y.
SERVICE ROAD 1+00 - 11+00	5602	132	165	5437
CTH U 1+00 7+05	1681	67	84	1597
*Fill Factor 25%				
<b>TOTAL</b>	<b>7283</b>			<b>7034</b>

TOPSOIL, SEED, FERTILIZER AND MULCH					
		SEED	SEED (125%)	FERTILIZER	EROSION MAT
LOCATION	TOPSOIL	TEMPORARY	MIX NO. 40	TYPE A	CLASS I TYPE A
	S.Y.	L.B.	L.B.	CWT	SY
SERVICE ROAD	1900	51	44	1.3	1900
CTH U	1400	38	32	0.9	1400
<b>TOTAL</b>	<b>3300</b>	<b>89</b>	<b>76</b>	<b>2</b>	<b>3300</b>

30 INCH CURB AND GUTTER TYPE D	
LOCATION	LENGTH
	FT
SERVICE ROAD	2030
CTH U	1100
<b>TOTAL</b>	<b>3130</b>

BREAKER RUN		
LOCATION	BASE THICKNESS	TON
	IN	
SERVICE ROAD	12	2200
CTH U	12	1700
<b>TOTAL</b>		<b>3900</b>

BASE AGGREGATE DENSE 3/4 INCH		
LOCATION	BASE THICKNESS	TON
DRIVEWAY 5+50 LT	4	3
DRIVEWAY 9+70 RT	4	3
DRIVEWAY 6+35 RT	4	3
DUCK CREEK TRAIL	3	77
<b>TOTAL</b>		<b>86</b>

BASE AGGREGATE DENSE 1 1/4 INCH		
LOCATION	BASE THICKNESS	TON
SERVICE ROAD	8	1100
CTH U	8	1400
SERVICE ROAD SIDEWALK	3	100
<b>TOTAL</b>		<b>2600</b>

HMA PAVEMENT		TYPE E-3.0	TACK COAT	PG 58-28
LOCATION	MAT THICKNESS	TON	GAL	TON
SERVICE ROAD	4	510	57	31
CTH U	4	450	50	27
<b>TOTAL</b>		<b>960</b>	<b>107</b>	<b>58</b>

ASPHALTIC SURFACE DRIVEWAYS AND FIELD ENTRANCE		
LOCATION	MAT THICKNESS	TON
DRIVEWAY 1+35 LT	2	2
DRIVEWAY 2+89 LT	2	2
DRIVEWAY 6+20 RT	2	2
DRIVEWAY 6+51 LT	2	2
DRIVEWAY 8+88 RT	2	2
DRIVEWAY 6+80 TO 10+60 LT	4	45
DRIVEWAY 1+00 TO 3+90 RT	4	25
DRIVEWAY 2+00 LT	4	20
<b>TOTAL</b>		<b>100</b>

CONCRETE DRIVEWAY	
LOCATION	SY
DRIVEWAY 6+00 RT	23
DRIVEWAY 8+85 RT	13
DRIVEWAY 9+65 RT	23
<b>TOTAL</b>	<b>59</b>

CONCRETE SIDEWALK	
LOCATION	SF
SERVICE ROAD	5750
CTH U	370
<b>TOTAL</b>	<b>6120</b>

DETECTABLE WARNING FIELD	
LOCATION	SF
CTH U	48
<b>TOTAL</b>	<b>48</b>

REMOVING SIDEWALK	
LOCATION	SF
SERVICE ROAD 3+20 TO 5+10 LT	113
<b>TOTAL</b>	<b>113</b>

SAWING		
LOCATION	CONCRETE	ASPHALT
1+00 TO 1+50	5	75
1+35 LT		15
2+85 LT		15
6+00 RT		19
6+15 LT		19
6+90 TO 11+50 LT		490
8+85 RT		11
1+00	5	30
1+00 TO 4+00 RT		196
2+10 LT		55
7+05		30
<b>TOTAL</b>	<b>10</b>	<b>955</b>

REMOVING CURB AND GUTTER	
LOCATION	LF
0+95 TO 5+43 LT	387
1+75 RT	38
11+00 RT	65
1+15 RT	36
<b>TOTAL</b>	<b>526</b>


ADJUSTING MANHOLE	
-------------------	--

**ONEIDA TRIBE OF INDIANS OF WISCONSIN  
SERVICE ROAD**


PROJECT NO.  
2013075  
DATE  
8/12/13

OTIE  
SHEET NO.  
4


TYPICAL EXISTING SECTION: CTH U




TYPICAL EXISTING SECTION: SERVICE ROAD



TYPICAL FINISHED SECTION: SERVICE ROAD  
STATION 1+50 TO STATION 10+75








LEGEND			
ITEM	UNIT	QUANTITY	
SILT FENCE	LF	430	
INLET PROTECTION TYPE 'B'	EACH	5	
INLET PROTECTION TYPE 'C'	EACH	14	
TEMPORARY DITCH CHECKS	LF	20	

SILT FENCE TO BE INSTALLED IN  
ACCORDANCE WITH THE WISCONSIN  
DEPARTMENT OF TRANSPORTATION STANDARD  
DETAIL DRAWING 8E9-6.

~~SILT FENCE TO BE PAID FOR AT CONTRACT PRICE, AS SILT FENCE, TYPE PREASSEMBLED.~~




TRAFFIC CONTROL  
 ONEIDA TRIBE OF INDIANS OF WISCONSIN  
 SERVICE ROAD RECONSTRUCTION

## TEMPORARY TRAFFIC CONTROL SCHEDULE


INSTALLATION CODE	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
QUANTITY	2	2	1	1	3	5	2	5	2	1
MUTCD REFERENCE	W20-3	W20-3	W20-3	W20-3	G20-2	TYPE III BARRICADE	R11-3	TYPE A WARNING LIGHTS		R11-3
SIZE	48"X48"	48"X48"	48"X48"	48"X48"	60"X24"	8' WIDE	60"X30"		6"X24"	60"X30"
SIGN										
NOTES	PLACE 1000 FT FROM CLOSURE	PLACE 500 FT FROM CLOSURE	PLACE 1000 FT FROM CLOSURE	PLACE 500 FT FROM CLOSURE	PLACE 500 FT PAST CONSTRUCTION LIMITS	PLACE TWO AT CONSTRUCTION LIMITS	INSTALL ON 8' WIDE TYPE III BARRICADE AT EACH MAIN INTERSECTION	INSTALL ON THE TYPE III BARRICADES	INSTALL UNDER SIGNS (C) OR (D)	INSTALL ON 8' WIDE TYPE III BARRICADE


NOTE: ALL TRAFFIC DEVICES SHALL CONFORM TO MUTCD. IN ADDITION TO THE DEVICES, THE CONTRACTOR IS REQUIRED TO IDENTIFY HAZARDOUS WORK AREAS AND SIGN THEM IN ACCORDANCE WITH THE MUTCD.




PERMANENT SIGNING SCHEDULE

ALIGNMENT	LOCATION	DESCRIPTION	QTY.	REFERENCE	SIZE	SQ. FEET	WOOD POSTS
SERVICE ROAD	4+15 RT	ONEIDA UNINCORPORATED	1				2
SERVICE ROAD	8+40 LT	SPEED LIMIT 30 MPH	1	R2-1	18"X24"	3.00	1
SERVICE ROAD	10+25 RT	CTH U	1	M1-6	24"X24"	4.00	1
SERVICE ROAD	10+25 RT	ARROW	1	M6-1	21"X15"	2.19	
SERVICE ROAD	11+00 RT	STOP	1	R1-1	24"X24"	4.00	1
CTH U	5+20 LT	CTH U	1	M1-6	24"X24"	4.00	1
CTH U	5+20 LT	ARROW	1	M6-1	21"X15"	2.19	
					TOTALS	19.38	6






1 TYPICAL PERMANENT SIGNING INSTALLATION  
10 NTS



2 TYPICAL TEMPORARY SIGNING INSTALLATION  
10 NTS







2 CONC. DRIVE APRON  
13 NTS


NO.	DATE	REVISION

CONSTRUCTION DETAILS
ONEIDA TRIBE OF INDIANS OF WISCONSIN SERVICE ROAD RECONSTRUCTION

PROJECT NO.	2013075
DATE	8/12/13
OTIE	
Sheet No.	9




**TYPE "H"**  
(APPROXIMATE WEIGHT 441 LBS.)  
FRAME..... 181 LBS.  
GRATE..... 146 LBS.  
CURB BOX..... 114 LBS.



**SPECIAL GRATE FOR TYPE "H" COVER**

(MEASURES 35 1/4" X 17 3/4" X 2")  
(APPROXIMATE WEIGHT 159 LBS.)  
GRATE..... 159 LBS.

(NOTED AS TYPE H-S ON DRAINAGE TABLE)



**LOGO DETAIL**




## GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.


DETAIL DRAWINGS FOR PROPOSED ALTERNATE DESIGNS FOR CATCH BASIN, MANHOLE AND INLET COVERS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL PROVIDING THAT SUCH ALTERNATE DESIGNS MAKE PROVISION FOR EQUIVALENT CAPACITY AND STRENGTH.

ROUND FRAMES AND COVERS SHALL HAVE CONTINUOUSLY MACHINED BEARING SURFACES TO PREVENT ROCKING AND RATTLING.

THE ACTUAL WEIGHT OF COVERS MAY VARY WITHIN 5 PERCENT, PLUS OR MINUS, OF THE APPROXIMATE WEIGHT.




NOTE: CURB BOX ADJUSTABLE 4" TO 9"




**TYPE "A"**

(APPROXIMATE WEIGHT 340 LBS.)  
FRAME..... 185 LBS.  
GRATE..... 71 LBS.  
CURB BOX..... 84 LBS.



**LOGO DETAIL**

NOTE:  
GRATE IS REVERSIBLE.



**SPECIAL GRATE FOR TYPE "A" COVER**

(MEASURES 19 3/4" X 17" X 1 7/8")  
GRATE..... 84 LBS.

(NOTED AS TYPE A-S ON DRAINAGE TABLE)

## INLET COVERS TYPE A, H, A-S, & H-S




STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED

6/5/2012


DATE

/S/ Jerry H. Zogg  
ROADWAY STANDARDS DEVELOPMENT  
ENGINEER



**TYPE "B"**  
(APPROXIMATE WEIGHT 405 LBS.)



FRAME..... 294 LBS.  
GRATE..... 111 LBS.



**ALTERNATIVE GRATE FOR  
TYPE "B" COVER**

(APPROXIMATE GRATE WEIGHT 134 LBS.)

USE WHERE PEDESTRIAN OR BICYCLE TRAFFIC IS POSSIBLE.  
NOTED AS TYPE B-A ON THE DRAINAGE TABLE



**TYPE "WM"**

(APPROXIMATE WEIGHT 648 LBS.)  
FRAME..... 355 LBS.  
GRATE..... 156 LBS.  
CURB BOX..... 137 LBS.

DIAGONAL SLOTS, SHALL BE ORIENTED  
TO THE DIRECTION OF FLOW AS ILLUSTRATED.  
GRATES ARE MANUFACTURED TO BE REVERSIBLE.





## GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING  
SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND  
THE APPLICABLE SPECIAL PROVISIONS.

DETAIL DRAWINGS FOR PROPOSED ALTERNATE DESIGNS FOR CATCH BASIN, MANHOLE  
AND INLET COVERS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL PROVIDING  
THAT SUCH ALTERNATE DESIGNS MAKE PROVISION FOR EQUIVALENT CAPACITY AND STRENGTH.

ROUND FRAMES AND COVERS SHALL HAVE CONTINUOUSLY MACHINED BEARING  
SURFACES TO PREVENT ROCKING AND RATTLING.


THE ACTUAL WEIGHT OF COVERS MAY VARY WITHIN 5 PERCENT, PLUS OR MINUS, OF  
THE APPROXIMATE WEIGHT.



**TYPE "C"**

(APPROXIMATE WEIGHT 259 LBS.)


FRAME..... 152 LBS.  
GRATE..... 107 LBS.



**ALTERNATIVE TYPE "MS"**

(APPROXIMATE GRATE WEIGHT 329 LBS.)

USE WHERE PEDESTRIAN OR BICYCLE TRAFFIC IS PERMITTED  
NOTED AS TYPE MS-A ON THE DRAINAGE TABLE



**TYPE "MS"**


(APPROXIMATE GRATE WEIGHT 268 LBS.)

USE ON FREEWAYS AND EXPRESSWAYS  
NOTED AS TYPE MS ON DRAINAGE TABLE


**INLET COVERS  
TYPE B, B-A, C, MS, MS-A, & WM**

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
6/5/2012 /S/ Jerry H. Zogg  
DATE ROADWAY STANDARDS DEVELOPMENT  
FHWA ENGINEER



HALF SECTION A-A



### GENERAL NOTES

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

DETAILED DRAWINGS FOR PROPOSED ALTERNATE DESIGNS FOR UNDERGROUND DRAINAGE STRUCTURES SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL PROVIDING THAT SUCH ALTERNATE DESIGNS MAKE PROVISION FOR EQUIVALENT CAPACITY AND STRENGTH.

ALL DRAINAGE STRUCTURES ARE DESIGNATED ON THE PLANS AS "MANHOLES 1-C", "CATCH BASINS 1-B", "INLETS 3-H", ETC. THE FIRST DIGIT DESIGNATES THE MASONRY PORTION OF THE STRUCTURE, AND THE FOLLOWING LETTER DESIGNATES THE TYPE OF COVER TO BE USED TO COMprise THE COMPLETE UNIT.

PRECAST REINFORCED BASES SHALL BE PLACED ON A BED OF MATERIAL AT LEAST 6 INCHES IN DEPTH, WHICH MEETS THE REQUIREMENTS OF GRANULAR BACKFILL. THIS BEDDING SHALL BE COMPAKTED AND PROVIDE UNIFORM SUPPORT FOR THE ENTIRE AREA OF THE BASE.

PRECAST REINFORCED CONE TOPS (ECCENTRIC OR CONCENTRIC) MAY BE USED ON CONCRETE BLOCK STRUCTURES. THE CONE TOPS SHALL BE INSTALLED ON A BED OF MORTAR.

ECCENTRIC CONE TOPS MAY BE USED ON ALL STRUCTURES, AND CONCENTRIC CONE TOPS SHALL BE USED ONLY ON STRUCTURES 5 FEET OR LESS IN DEPTH, UNLESS OTHERWISE DIRECTED BY THE ENGINEER.

STEPS CONFORMING TO AASHTO M 199 SHALL BE INSTALLED IN ALL STRUCTURES OVER 5 FEET IN DEPTH.

SOLID ALUMINUM STEPS SHALL HAVE A MINIMUM CROSS SECTIONAL DIMENSION OF 0.75 INCH. ALUMINUM SURFACES TO BE EMBEDDED IN CONCRETE SHALL BE GIVEN ONE COAT OF SUITABLE QUALITY PAINT, SUCH AS ZINC CHROMATE PRIMER CONFORMING TO FEDERAL SPECIFICATION TT-P-645 OR EQUIVALENT.


ALL BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2 INCHES CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

PRECAST REINFORCED CONCRETE RISERS MAY BE PLACED WITH TONGUE UP OR DOWN.


ALL PRECAST INLET UNITS AND MANHOLES SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF AASHTO DESIGNATION M 199.

\* USE 2'-0" DIAMETER OPENING WITH TYPE "C", "L" AND "J" COVERS, OR 3'-0" DIAMETER WITH TYPE "K" AND "M" COVERS.

① 2 COURSES 6" BLOCK.



SECTION B-B  
REINFORCED CONCRETE



CONCRETE BLOCK

MANHOLES TYPE 1

### MANHOLES TYPE 1


STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




APPROVED  
9/9/05 /S/ Jerry H. Zogg  
DATE ROADWAY STANDARDS DEVELOPMENT  
FHWA ENGINEER





# 8D1: Concrete Curb, Concrete Curb & Gutter and Ties





SECTION B-B

## GENERAL NOTES


USE THE TYPE 3 RAMP ONLY WHEN A TYPE 1 OR TYPE 2 CANNOT BE ACHIEVED BECAUSE OF FIELD CONDITIONS.


DETECTABLE WARNING FIELDS THAT ARE INSTALLED AS A GROUP OR SIDE BY SIDE, SHALL BE FROM THE SAME MANUFACTURER.

- ① WHEN THIS DISTANCE IS LESS THAN 6'-0" IT MAY BE DIFFICULT TO ACHIEVE A 12H:IV SLOPE, OR FLATTER, ON THE RAMP. REDUCE CURB HEIGHT IN TRIANGLE AREA TO ACHIEVE 12H:IV SLOPE, OR FLATTER, ON RAMP. 2" MINIMUM CURB HEIGHT.
- ② GRADE CHANGE BETWEEN GUTTER FLAG SLOPE AND THE CURB RAMP SLOPE SHALL NOT EXCEED 1%. PROVIDE DRAINAGE AWAY FROM CURB RAMP AT GUTTER FLAG INTERFACE.
- ③  $\pm 0.5\%$  CONSTRUCTION TOLERANCE IN SIDEWALK CROSS SLOPE. THE SIDEWALK CROSS SLOPE SHALL NOT EXCEED 2% WITHOUT PRIOR APPROVAL FROM THE ENGINEER.


## LEGEND

- $\frac{1}{2}$ " EXPANSION JOINT-SIDEWALK
- - - CONTRACTION JOINT FIELD LOCATED
- ||||| PAVEMENT MARKING CROSSWALK (WHITE)
- ALTERNATIVE LAYOUT


PLAN VIEW  
TYPE 3 RAMP  
(OUTSIDE OF CROSSWALK AREA)CURB RAMPS  
TYPES 2 AND 3STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION




PLAN VIEW  
TYPICAL APPLICATION OF SILT FENCE



### SILT FENCE AT MEDIAN SURFACE DRAINS



SILT FENCE




JOINING TWO LENGTHS OF SILT FENCE<sup>⑤</sup>


### GENERAL NOTES

DETAILS OF CONSTRUCTION NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND APPLICABLE SPECIAL PROVISIONS.

- ① HORIZONTAL BRACE REQUIRED WITH 2" X 4" WOODEN FRAME OR EQUIVALENT AT TOP OF POSTS.
- ② FOR MANUAL INSTALLATIONS THE TRENCH SHALL BE A MINIMUM OF 4" WIDE & 6" DEEP TO BURY AND ANCHOR THE GEOTEXTILE FABRIC. FOLD MATERIAL TO FIT TRENCH AND BACKFILL & COMPACT TRENCH WITH EXCAVATED SOIL.
- ③ WOOD POSTS SHALL BE A MINIMUM SIZE OF 1/8" X 1/8" OF OAK OR HICKORY.
- ④ SILT FENCE TO EXTEND ACROSS THE TOP OF THE PIPE.
- ⑤ CONSTRUCT SILT FENCE FROM A CONTINUOUS ROLL IF POSSIBLE BY CUTTING LENGTHS TO AVOID JOINTS. IF A JOINT IS NECESSARY USE ONE OF THE FOLLOWING TWO METHODS; A) OVERLAP THE END POSTS AND TWIST, OR ROTATE, AT LEAST 180 DEGREES, B) HOOK THE END OF EACH SILT FENCE LENGTH.





TRENCH DETAIL



SILT FENCE TIE BACK  
(WHEN REQUIRED BY THE ENGINEER)

SILT FENCE	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED 4-29-05 DATE	/S/ Beth Cannestra CHIEF ROADWAY DEVELOPMENT ENGINEER FHWA



### INLET PROTECTION, TYPE A

#### GENERAL NOTES

INLET PROTECTION DEVICES SHALL BE MAINTAINED OR REPLACED AT THE DIRECTION OF THE ENGINEER.


MANUFACTURED ALTERNATIVES APPROVED AND LISTED ON THE DEPARTMENT'S EROSION CONTROL PRODUCT ACCEPTABILITY LIST MAY BE SUBSTITUTED.

WHEN REMOVING OR MAINTAINING INLET PROTECTION, CARE SHALL BE TAKEN SO THAT THE SEDIMENT TRAPPED ON THE GEOTEXTILE FABRIC DOES NOT FALL INTO THE INLET. ANY MATERIAL FALLING INTO THE INLET SHALL BE REMOVED IMMEDIATELY.

① FINISHED SIZE, INCLUDING FLAP POCKETS WHERE REQUIRED, SHALL EXTEND A MINIMUM OF 10" AROUND THE PERIMETER TO FACILITATE MAINTENANCE OR REMOVAL.


② FOR INLET PROTECTION, TYPE C (WITH CURB BOX), AN ADDITIONAL 18" OF FABRIC IS WRAPPED AROUND THE WOOD AND SECURED WITH STAPLES. THE WOOD SHALL NOT BLOCK THE ENTIRE HEIGHT OF THE CURB BOX OPENING.

③ FLAP POCKETS SHALL BE LARGE ENOUGH TO ACCEPT WOOD 2x4.



### INLET PROTECTION, TYPE B (WITHOUT CURB BOX)

(CAN BE INSTALLED IN ANY INLET WITHOUT A CURB BOX)



### INLET PROTECTION, TYPE C (WITH CURB BOX)

#### INSTALLATION NOTES

##### TYPE B & C

TRIM EXCESS FABRIC IN THE FLOW LINE TO WITHIN 3" OF THE GRATE.

THE CONTRACTOR SHALL DEMONSTRATE A METHOD OF MAINTENANCE, USING A SEWN FLAP, HAND HOLDS OR OTHER METHOD TO PREVENT ACCUMULATED SEDIMENT FROM ENTERING THE INLET.


##### TYPE D

DO NOT INSTALL INLET PROTECTION TYPE D IN INLETS SHALLOWER THAN 30", MEASURED FROM THE BOTTOM OF THE INLET TO THE TOP OF THE GRATE.

TRIM EXCESS FABRIC IN THE FLOW LINE TO WITHIN 3" OF THE GRATE.

THE INSTALLED BAG SHALL HAVE A MINIMUM SIDE CLEARANCE, BETWEEN THE INLET WALLS AND THE BAG, MEASURED AT THE BOTTOM OF THE OVERFLOW HOLES, OF 3". WHERE NECESSARY THE CONTRACTOR SHALL CINCH THE BAG, USING PLASTIC ZIP TIES, TO ACHIEVE THE 3" CLEARANCE. THE TIES SHALL BE PLACED AT A MAXIMUM OF 4" FROM THE BOTTOM OF THE BAG.

INLET SPECIFICATIONS AS PER THE PLAN  
DIMENSION LENGTH AND WIDTH TO MATCH





### INLET PROTECTION, TYPE D


(CAN BE INSTALLED IN ANY INLET TYPE WITH  
OR WITHOUT A CURB BOX AS PER NOTE ②)

#### INLET PROTECTION TYPE A, B, C, AND D

STATE OF WISCONSIN  
DEPARTMENT OF TRANSPORTATION

APPROVED  
10/16/02 /S/ Beth Cannestra  
DATE  
FHWA  
CHIEF ROADWAY DEVELOPMENT ENGINEER





STORM SEWER  
ONEIDA TRIBE OF INDIANS OF WISCONSIN  
SERVICE ROAD RECONSTRUCTION

STORM SEWER SCHEDULE						
STRUCTURE ID	STATION	LOCATION	OFFSET	RIM ELEVATION	INLET TYPE 3	MANHOLE TYPE 1 SPECIAL *
EX	0+92	SERVICE RD	17.0 LT			
1	1+53	SERVICE RD	11.25 LT	713.96		1
2	1+53	SERVICE RD	11.25 RT	713.96	1	1
3	4+53	SERVICE RD	11.25 LT	731.55		1
4	4+53	SERVICE RD	11.25 RT	731.55	1	1
5	7+53	SERVICE RD	11.25 LT	741.66		1
6	7+53	SERVICE RD	11.25 RT	741.66	1	1
7	8+77	SERVICE RD	11.25 LT	742.85		1
8	8+77	SERVICE RD	11.25 RT	742.85	1	1
9	10+67	SERVICE RD	11.25 LT	743.67		1
10	5+58	CTH U	16.25 RT	745.40	1	1
11	4+42	CTH U	16.25 LT	743.80	1	1
12	4+42	CTH U	16.25 RT	743.83		1
13	3+00	CTH U	16.25 RT	744.10	1	1
14	3+00	CTH U	16.25 LT	744.10	1	1
			TOTAL	8	6	14

\* MANHOLE TYPE 1 SPECIAL HAS A REVISED OPENING OF 24 INCH BY 30 INCH RECTANGLE TO FIT  
INLET COVER TYPE C

PIPE ID	FROM STRUCTURE	TO STRUCTURE	INLET ELEVATION	OUTLET ELEVATION	12 - INCH	24 - INCH	SLOPE %
					LENGTH FEET	LENGTH FEET	
1	EX	1	709.86	706.60		61	5.34
2	1	2	710.31	709.86	23		2.00
3	1	3	726.36	709.86		300	5.50
4	3	4	726.81	726.36	23		2.00
5	3	5	735.36	726.36		300	3.00
6	5	6	735.81	735.36	23		2.00
7	5	7	736.60	735.36		124	1.00
8	7	8	737.05	736.60	23.0		2.00
9	7	9	738.54	736.60		194	1.00
10	EX PIPE	9	740.85	740.71	7		1.00
11	9	10	740.46	738.54	96		2.00
12	9	12	739.29	738.54	75		1.00
13	12	11	740.00	739.29	36		1.00
14	12	13	740.68	739.29	139		1.00
15	13	14	741.00	740.68	33		1.00
				TOTAL	478	979	


PROJECT NO.  
2013075

DATE  
8/12/13


OTIE



SHEET NO.



19



**PLAN SHEET**  
**ONEIDA TRIBE OF INDIANS OF WISCONSIN**  
**SERVICE ROAD RECONSTRUCTION**









## DUCK CREEK TRAIL RELOCATION

POINT	STATION	OFFSET	ELEVATION
L	5+64 LT	52.11	744.65
M	5+94 LT	26.78	746.99
N	5+95 LT	34.29	747.29
O	5+98 LT	48.89	744.65
P	6+46 LT	23.07	748.29
Q	6+47 LT	28.07	748.49
R	6+52 LT	39.25	744.65
S	7+05 LT	27.53	745.10


 PLAN SHEET  
 ONEIDA TRIBE OF INDIANS OF WISCONSIN  
 SERVICE ROAD RECONSTRUCTION

 PROJECT NO.  
 2013075

 DATE  
 8/12/13







OTIE

SHEET NO.

23







CROSS SECTIONS  
ONEIDA TRIBE OF INDIANS OF WISCONSIN  
SERVICE ROAD RECONSTRUCTION

PROJECT NO.  
2013075  
DATE  
8/12/13  
OTIE  
SHEET NO.  
24



CROSS SECTIONS  
ONEIDA TRIBE OF INDIANS OF WISCONSIN  
SERVICE ROAD RECONSTRUCTION







PROJECT NO.  
2013075  
DATE  
8/12/13  
OTIE  
SHEET NO.  
25



CROSS SECTIONS  
ONEIDA TRIBE OF INDIANS OF WISCONSIN  
SERVICE ROAD RECONSTRUCTION

PROJECT NO.  
2013075  
DATE  
8/12/13  
OTIE  
SHEET NO.

26



CROSS SECTIONS  
ONEIDA TRIBE OF INDIANS OF WISCONSIN  
SERVICE ROAD RECONSTRUCTION





PROJECT NO.  
2013075







DATE  
8/12/13

OTIE

SHEET NO.







27





CROSS SECTIONS  
ONEIDA TRIBE OF INDIANS OF WISCONSIN  
SERVICE ROAD RECONSTRUCTION

PROJECT NO.  
2013075  
DATE  
8/12/13  
OTIE  
SHEET NO.  
29





REVISION

NO.	DATE	REVISION

CROSS SECTIONS  
ONEIDA TRIBE OF INDIANS OF WISCONSIN  
SERVICE ROAD RECONSTRUCTION

PROJECT NO.  
2013075  
DATE  
8/12/13  
OTIE  
SHEET NO.  
30



EARTHWORK TABULATION SHEET  
ONEIDA TRIBE OF INDIANS OF WISCONSIN  
SERVICE ROAD RECONSTRUCTION

PROJECT NO.  
2013075

DATE  
8/12/13

OTIE

SHEET NO.

31

Service Road Total Volume Table								Service Road Total Volume Table							
Station	Cut Area	Fill Area	Cut Vol	Fill Vol	Cum Cut Vol	Cum Fill Vol	Net Vol	Station	Cut Area	Fill Area	Cut Vol	Fill Vol	Cum Cut Vol	Cum Fill Vol	Net Vol
1+00.00	42.73	0.00	0.00	0.00	0.00	0.00	0.00	1+00.00	69.67	0.22	0.00	0.00	0.00	0.00	0.00
1+52.53	127.21	2.52	165.32	2.45	165.32	2.45	162.86	1+50.00	73.91	0.03	132.94	0.24	132.94	0.24	132.71
2+00.00	117.48	7.34	215.10	8.67	380.42	11.12	369.30	2+00.00	61.40	1.43	125.29	1.35	258.23	1.59	256.64
2+50.00	136.86	4.90	235.51	11.33	615.93	22.45	593.47	2+50.00	65.48	1.38	117.72	2.52	375.95	4.11	371.84
3+00.00	151.14	2.10	266.67	6.48	882.59	28.93	853.66	3+00.00	76.38	0.36	131.83	1.57	507.77	5.68	502.09
3+50.00	155.99	7.52	284.38	8.91	1166.97	37.84	1129.13	3+50.00	83.25	0.28	148.47	0.55	656.24	6.24	650.01
4+00.00	159.55	3.12	292.16	9.86	1459.13	47.69	1411.44	4+00.00	89.37	0.00	159.83	0.26	816.08	6.49	809.58
4+52.63	142.95	9.81	294.84	12.61	1753.97	60.30	1693.67	4+45.26	71.58	0.78	134.90	0.65	950.98	7.15	943.83
5+00.00	153.74	2.92	260.26	11.16	2014.22	71.46	1942.76	5+00.00	54.19	10.82	127.48	11.76	1078.46	18.90	1059.56
5+50.00	123.59	11.94	256.79	13.76	2271.01	85.22	2185.79	5+50.00	82.41	0.98	125.02	11.10	1203.48	30.00	1173.47
6+00.00	125.62	10.26	230.75	20.55	2501.76	105.77	2395.99	6+00.00	99.58	0.43	166.86	1.28	1370.33	31.29	1339.05
6+50.00	137.94	6.38	244.04	15.40	2745.80	121.17	2624.63	6+50.00	79.80	10.78	165.61	9.84	1535.95	41.13	1494.82
7+00.00	166.10	1.49	281.52	7.29	3027.33	128.46	2898.86	7+00.00	64.07	15.35	133.15	23.25	1669.10	64.38	1604.72
7+52.50	184.68	0.01	341.01	1.46	3368.34	129.92	3238.42	7+05.00	64.09	15.70	11.87	2.88	1680.97	67.25	1613.71
8+00.00	186.34	0.00	326.39	0.01	3694.73	129.93	3564.80								
8+50.00	195.54	0.13	353.87	0.12	4048.60	130.06	3918.55								
8+76.96	217.43	0.00	206.17	0.07	4254.77	130.12	4124.64								
9+00.00	209.05	0.00	181.98	0.00	4436.75	130.13	4306.62								
9+50.00	204.65	0.07	383.47	0.06	4820.22	130.19	4690.03								
10+00.00	204.45	0.02	379.39	0.08	5199.61	130.27	5069.34								
10+50.00	169.31	0.87	341.78	0.88	5541.39	131.15	5410.23								
10+70.00	0.00	0.00	61.05	0.37	5602.44	131.53	5470.91								
11+00.00	0.00	0.00	0.00	0.00	5602.44	131.53	5470.91								

NO. DATE REVISION

PROJECT NO.

2013075

DATE

8/12/13

OTIE

SHEET NO.

31